Demo Script: DevCon 2024

Download and Save Sample Code

1. Download twinBASIC BETA 504
2. Extract from Zip folder
3. Open twinBASIC > **Sample 4**
4. Enter Project Name: Demo2024 (*Do not put spaces in the name*)
5. Save as: %tmp%\Demo2024\Demo2024.twinproj
   1. Navigate to: %tmp%
   2. Create folder named: Demo2024
   3. Filename: Demo2024.twinproj

Customize the Addin Name and Description

Next, let's customize the friendly name and description of our addin. This is the info that appears in the VBA Add-in Manager dialog box.

1. Go to **dllRegistration.twin** > **DllRegisterServer**
2. In the "FriendlyName" line, replace *AddinProjectName* with "DevCon 2024 Demo"
3. In the "Description" line, replace *AddinProjectName* with "`Create a strongly-typed collection class from an existing VBA class object.`"
4. Save the project
5. Build the project
6. Launch M:\Repos\NLS\DevCon2024\DevCon2024.accdb
7. Switch to VBA: `Ctrl` + `G`
8. Dock the add-in window
9. Go to "Add-Ins" > "Toggle myToolWindow Visibility"
10. Go to "Add-Ins" > "Add-in Manager"
    - Point out the "DevCon 2024 Demo" item with description below
11. Close "Add-In Manager" window

Create the Tool Window Controls

Next, we're going to customize the controls that appear on the tool window. I'll explain what these controls will be used for in a minute. For now, all you need to know is that we are adding two text boxes, a command button, and a label to hold a version number.

1. Open myToolWindow.tbcontrol
2. Select all controls and delete them
3. Click DIAGNOSTICS error to go to myToolWindow.twin and **delete all dead code**
4. Select form and set the following properties:

- Height: 1700
- Width: 2550

5. Create a text box and set the following properties:
   - Name: `tbObjName`
   - Anchors > Right: ☑ True
   - Height: 300
   - Left: 150
   - Text: *{blank}*
   - TextHint: `Object Class Name`
   - Top: 150
   - Width: 2250
6. Create a text box and set the following properties:
   - Name: `tbCollName`
   - Anchors > Right: ☑ True
   - Height: 300
   - Left: 150
   - Text: *{blank}*
   - TextHint: `Collection Class Name`
   - Top: 600
   - Width: 2250
7. Create a button and set the following properties:
   - Name: `btnCreateClass`
   - Anchors > Right: ☑ True
   - Caption: `Create Collection Class`
   - Height: 450
   - Left: 150
   - Top: 1050
   - Width: 2250
8. Create a version label
   - Caption: Version {hhmm}

Edit the Code in myToolWindow.twin

1. Delete the `Timer1_Timer()` and `HelloWorld_Click()` subroutines
2. Add a Click event handler for btnCreateClass using the code below

```
Private Sub btnCreateClass_Click()
    MsgBox "Object class name: " & Me.tbObjName.Text & vbNewLine & _
           "Collection class name: " & Me.tbCollName.Text, vbInformation, _
"Create Class"
End Sub
```

1. Make sure Access is closed then **Build** the tB project
2. Reopen Access and switch to VBA
3. Enter sample text `oVehicle` for object class name and `collVehicles` for collection class name then click [Create Collection Class]

Build and Test the Addin on a Different Machine and Bitness

The following instructions assume you are building on a machine with 32-bit Office (mjw20), but installing on a machine with 64-bit Office (e.g., gbm18):

1. Ensure "**win64**" is selected in dropdown
2. **File** > **Build**
3. I copied M:\Repos\NLS\DevCon2024\Build\DevCon2024_win64.dll to %fb%\12114\DevCon2024_win64.dll (I will test registering it tomorrow on gbm18)
4. Open a non-admin cmd prompt
5. Run: regsvr32 DevCon2024_win64.dll
    ○ Receive message: "DllRegisterServer in DevCon2024_win64.dll succeeded."
6. Open Word (or Excel) - The add-in appears.

Copy and Paste Working VBA Code into twinBASIC

1. Add a standard code module named "MyModule":
    1. Right-click Sources > **Add** > **Add Module (.TWIN supporting Unicode)**
2. Go to 🅰️Strongly-Typed Collections: The Easy Way
    1. Copy and paste the 🅰️GetGuidBasedTempPath code
    2. Copy and paste the 🅰️FileWrite code
3. Handle "Unrecognized datatype symbol 'Scripting'" error in DIAGNOSTICS pane:
    1. Go to **Project** > **References**
    2. Switch to "Available COM References" tab
    3. Search for "script" and then click the "Microsoft Scripting Runtime" reference
    4. Click [Save Changes]

Add fafalone's WinDevLib Package for API Calls

1. **Project** > **References…**
2. Switch to "Available Packages" tab
3. Search for "windows"
4. Check box next to "☑ Windows Development Library for twinBASIC vX.Y.ZZZ"
    ○ The package will immediately begin downloading in the background
    ○ When the download finishes, the name will change to "☑ [IMPORTED] Windows Development Library for twinBASIC vX.Y.ZZZ"
    ○ NOTE: "WinDevLib for Implements" is a different package
5. Click [Save Changes]
6. Comment out (or delete) API `Declare` lines throughout the project
    ○ Be aware that if you used non-standard `Alias` names, you may need to adjust your API calls to match the standard versions used in WinDevLib
    ○ **myAddIn.twin**:
        ▪ Delete Private Type RECT structure
        ▪ Delete GetClientRect() function declare

- ○ **InterProcess.twin**:
    - Delete `GetCurrentProcessId()` function declare line...
    - ...through `Type UUID` structure
- ○ **MyModule.twin**:
    - Delete `Sleep` sub declare
    - Comment out `CoCreateGuid` function declare and highlight the failure to compile due to the stricter typing of `id As UUID` in WinDevLib versus `id As Any` in my code
    - Uncomment the `CoCreateGuid` function to show that explicit API declares override the WinDevLib versions

7. Pass Unicode strings directly to API declare functions
    - ○ Most string-related API functions have ANSI and Unicode versions ("A" and "W" for "ANSI" and "Wide", respectively)
    - ○ Lots of legacy VB6/VBA code use the ANSI version of API functions
    - ○ WinDevLib encourages the use of Unicode versions by default
    - ○ This means that code that passes input strings to API functions may require wrapping the string in `StrPtr()` (or removing `StrPtr()`) from your existing code
    - ○ ☐ Remove `StrPtr()` from calls to `FindWindowEx()` in InterProcess.callerApplicationObject
    - ○ ☐ Convert final argument from `0&` to `vbNullString` for calls to `FindWindowEx()` in InterProcess.callerApplicationObject

---